

Safety Data Sheet

according to UK REACH Regulation

OLI-PUR Verdünner V 15

Revision date: 05.11.2025

Product code: A01975

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

OLI-PUR Verdünner V 15

UFI: GV02-UVDP-EN0H-HHY6

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Process regulator or aid

1.3. Details of the supplier of the safety data sheet

Company name:	Oli Lacke GmbH	
Street:	Bahnhofstrasse 22	
Place:	D-09244 Lichtenau	
Telephone:	+49 37208 84200	Telefax: +49 37208 84268
e-mail:	info@oli-lacke.de	
Contact person:	Gemeins.	Telephone: +49(0)361/730730
	Gifinformationszentrum Erfurt	
Internet:	www.oli-lacke.de	

1.4. Emergency telephone number: Gemeins. Gifinformationszentrum Erfurt
+49(0)361/730730

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**Flam. Liq. 3; H226
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**n-butyl acetate
2-methoxy-1-methylethyl acetate**Signal word:** Warning**Pictograms:****Hazard statements**H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

according to UK REACH Regulation

OLI-PUR Verdünner V 15

Revision date: 05.11.2025

Product code: A01975

Page 2 of 9

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P370+P378	In case of fire: Use ... to extinguish.
P233	Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
123-86-4	n-butyl acetate			95 - < 100 %
	204-658-1	607-025-00-1	01-2119485493-29-XXXX	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
108-65-6	2-methoxy-1-methylethyl acetate			5 - < 10 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3, STOT SE 3; H226 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	5 - < 10 %
	dermal: LD50 = 7500 mg/kg; oral: LD50 = 8532 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After contact with eyes

Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse

Safety Data Sheet

according to UK REACH Regulation

OLI-PUR Verdünner V 15

Revision date: 05.11.2025

Product code: A01975

Page 3 of 9

immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Impaired consciousness

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a doctor.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam. Carbon dioxide (CO₂). Extinguishing powder. Water mist

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Hazardous decomposition products: carbon black Danger of serious damage to health by prolonged exposure. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking. Provide adequate ventilation. In case of fire and/or explosion do not breathe fumes. Safe handling: see section 7 Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Observe in addition any national regulations! In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**Other information**

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

See section 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Even after use and until complete evaporation of the flammable components, there is still a danger of an explosive steam-air mixture forming. Only use the material in places where open light, fire and other flammable sources can be kept away. Take precautionary measures against static discharges. Use explosion-proof electrical equipment. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Safety Data Sheet

according to UK REACH Regulation

OLI-PUR Verdünner V 15

Revision date: 05.11.2025

Product code: A01975

Page 4 of 9

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles When using do not eat, drink or smoke. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Concentrated vapours are heavier than air. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands before breaks and after work. Do not eat, drink, smoke or sneeze at the workplace.

Further information on handling

Observe in addition any national regulations!

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Betriebssicherheitsverordnung (BetrSichV)

Hints on joint storage

Keep away from: Acids Alkali (lye) Oxidizing agent

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place. Keep away from heat. Follow the instructions for use on the label. Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Use protective skin cream before handling the product.

Skin protection

Protective clothing: Natural fibres (e.g. cotton) heat-resistant synthetic fibres

Safety Data Sheet

according to UK REACH Regulation

OLI-PUR Verdünner V 15

Revision date: 05.11.2025

Product code: A01975

Page 5 of 9

Respiratory protection

During spraying wear suitable respiratory equipment. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
Colour:

Test method**Changes in the physical state**

Flash point:	> 23 °C	DIN EN ISO 1523
Lower explosion limits:	1,2 g/m ³	
Upper explosion limits:	10,6 g/m ³	
Auto-ignition temperature:	315 °C	
Decomposition temperature:		ASTM D 2879-86
Flow time: (at 20 °C)		Verarbeitungsfertig
Vapour pressure: (at 20 °C)	14 hPa	
Density (at 20 °C):	0,885 g/cm ³	g/cm ³ ISO 2811

9.2. Other information**Other safety characteristics**

Solvent separation test: < 3 %
Solvent content: 100 %

Further Information**SECTION 10: Stability and reactivity****10.1. Reactivity**

refer to chapter 7. No further action is necessary.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reactions with: Alkalis (alkalis), concentrated. Acid, concentrated. Oxidizing agents, strong.

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapours.

10.5. Incompatible materials

Rubber articles

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Nitrogen oxides (NO_x).

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation**

Safety Data Sheet

according to UK REACH Regulation

OLI-PUR Verdünner V 15

Revision date: 05.11.2025

Product code: A01975

Page 6 of 9

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 mg/kg	8532	Rat	RTECS
	dermal	LD50 mg/kg	7500	Rabbit	

Carcinogenic/mutagenic/toxic effects for reproduction

The components in this formulation do not meet the criteria for classification as CMR category 1 or 2.

Additional information on tests

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information**12.1. Toxicity**

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50	161 mg/l	96 h	Pimephales promelas	
	Acute crustacea toxicity	EC50	408 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-65-6	2-methoxy-1-methylethyl acetate	0,43

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of UK REACH.

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Safety Data Sheet

according to UK REACH Regulation

OLI-PUR Verdünner V 15

Revision date: 05.11.2025

Product code: A01975

Page 7 of 9

Disposal recommendations

Do not allow to enter into surface water or drains.

Dispose according to legislation.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint related material
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint related material
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint related material
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Special Provisions: 163, 223, 367, 955

Safety Data Sheet

according to UK REACH Regulation

OLI-PUR Verdünner V 15

Revision date: 05.11.2025

Product code: A01975

Page 8 of 9

Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint related material
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3
 Special Provisions: A3 A72 A192
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

Other applicable information (air transport)

00000000005: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

refer to chapter 7. No further action is necessary.

14.7. Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 40

2010/75/EU (VOC): 885 g/l

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

according to UK REACH Regulation

OLI-PUR Verdünner V 15

Revision date: 05.11.2025

Product code: A01975

Page 9 of 9

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.